



REINFORCED STRUT FOR DOOR OVER 3759 mm (148 in.) WIDTH
TORSION SPRING
DRUM
HEAD-ROOM
DOOR HEIGHT
DOOR WIDTH
GROOVES NOT ILLUSTRATED
EXTERIOR FINISHING BAKE-ON POLYESTER PAINT
INTERIOR FINISHING BAKE-ON POLYESTER PAINT
REINFORCEMENT METAL PLATE 14 GA.
HIGHT PRESSURE POLYURETHANE INJECTED DENSITY: 40kg/m³ (2.5 lbs/ft³)
PVC WEATHERSTRIPPING DUAL EXTRUSION.THERMAL-BRAKE. INFILTRATION 0.033 L/S-M (ASTM -E283)
PVC BOTTOM SEAL
PVC EXTRUSION
INSULATED GLAZED SECTION
PANORAMIC GLAZING SECTION
PCV FRAME
THERMOPANE 25 mm (1 in.)
FLEXIBLE WEATHER-STRIPPING
ALUMINIUM EXTRUSION FRAME
THERMOPANE 16 mm (5/8 in.)
PVC MOULDING
DRY PINE KD 6-8% GRADE 4
VERTICAL TRACKS
A-A
B-B
C-C
D-D

Door model : G5000
 Thickness : 45mm (1-3/4")
 RSI : 2.8 (R16)
 Exterior finishing : 26 ga. Steel
 Interior finishing : 26 ga. Steel
 Finish : Woodgrain
 Exterior colour :
 Interior colour :

# DOOR	QTY	WIDTH	HEIGHT	NB OF SECTION	GLAZED SECTIONS				OPERATION	OPTIONS	
					NB OF GLAZED SECTION	MODEL	QTY PANES	SIZES			
								WIDTH			HEIGHT

GARAGA INC.

PAGE : 1 OF 2

OVERHEAD GARAGE DOOR

PROJECT :

DISTRIB. :

ARCHITECT :

CONTRACTOR :

DATE :